

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number
WO 2004/042993 A1

(51) International Patent Classification⁷: **H04L 1/18**,
12/56, H04Q 7/22

Christoph [DE/DE]; c/o Philips Intellectual Property &
Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).

(21) International Application Number:
PCT/IB2003/004958

(74) Agent: **MEYER, Michael**; Philips Intellectual Property &
Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).

(22) International Filing Date:
6 November 2003 (06.11.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
102 52 536.6 8 November 2002 (08.11.2002) DE

(71) Applicant (*for DE only*): **PHILIPS INTELLECTUAL
PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except DE, US*):
KONINKLIJKE PHILIPS ELECTRONICS N.V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).

(72) Inventor; and


Published:

(75) Inventor/Applicant (*for US only*): **HERRMANN,**

— with international search report

[Continued on next page]

(54) Title: DATA TRANSMISSION SYSTEM



Ctrl:												
S	NSNRI	Qid	N	TSN	...	TSN	...	Qid	N	TSN	...	TSN
1	3	3	1	3	...	3	...					

S: 0: No SNRI-list follows
1: SNRI-list follows

NSNRI: Count of priority classes, for which entries are present.

Qid: Priority class to which the SNI list refers

N: Number of TSNs that follow

TSN: TSN of a MAC-hs PDU, which is still under retransmission

(57) Abstract: In order to minimize the overall delay when transmitting data via the HS-DSCH in UMTS, provisions should be made that an RLC entity on the UE side receives RLC PDUs carried by the HS-DSCH as early as possible from the MAC-hs layer, while at the same time keeping the right sequence of these RLC PDUs. In accordance with the present invention, the scheduler in Node B is allowed to send a list of TSNs of MAC-hs PDUs which are still under retransmission to the receiver, such as a mobile station. Such a list may also be sent for MAC-hs PDUs for which the transmission was aborted but a new transmission is intended. Advantageously, this may allow to avoid "useless gaps" in a reordering buffer of the receiver and, as such, may allow for an efficient data transmission.

WO 2004/042993 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.